



Clow Valve Co.

902 South 2nd Street
Oskaloosa, IA 52577

Telephone: 641 673-8611
Fax: 641 673-8269

CERTIFICATE OF COMPLIANCE & TESTING

MUD VALVES MODEL F3075T & F3085T

CLOW MUD VALVES ARE HEAVY DUTY FLANGED END TYPE FACED AND DRILLED TO ANSI 125 TEMPLATE WITH RISING OR NON-RISING STEMS. MUD VALVES ARE AVAILABLE WITH EXTENSION COUPLING, 2" SQUARE OPERATING NUT OR HANDWHEEL.

THE FRAME, YOKE AND GATE ARE STURDILY PROPORTIONED FOR STRENGTH AND RIGIDTY, MADE OF CAST IRON CONFORMING TO ASTM A126 CL.B.

THE STEM AND STEM NUT ARE COPPER ALLOW CONFORMING TO ASTM B584.

THE GATE SEAT IS SEAMLESS MOLDED BUNA-N RUBBER TAPERED TO MATE WITH COPPER ALLOW SEAT RING TO PROVIDE POSITIVE SEAL.

VALVES ARE SUITABLE FOR USE IN CHLORINATED WATER.

MUD VALVES ARE RECOMMENDED FOR USE IN APPLICATIONS WITH LOW SEATING OR UNSEATING PRESSURES ONLY.

VALVES ARE MANUFACTURED PER MATERIALS AND DIMENSIONS SHOWN IN CLOW VALVE COMPANY CATALOG.